

**1 D+H Mechatronic (english)****1.1 VLD Series - Drives****1.1.1 BSY+ linear lock drive - VLD 51/038-BSY+****24 V DC / 1 A / 500 N / 38 mm stroke****Performance features:**

Electromotive drive unit for the integrated mounting in the window profile. The drive is equipped with microprocessor-controlled motor and synchronous electronic BSY+ for communication and sequential control in conjunction with D+H BSY+ window opening drives. For operating standard latch pane fittings in the window profile. Can be used for openings for smoke exhaust; D+H Euro SHEV in accordance with EN 12101-2; and for daily ventilation. Drive functions and performance features are individually programmable via the D+H software SCS. VP signal of connected BSY+ opening actuators must be activated. Running and locking direction can be set via slide switch. A manual emergency release is possible with a special tool.

**Technical data:**

Operating voltage: 24 V DC /  $\pm 20$  %  
Current consumption: 1 A  
Duty cycle: 30 % (ON: 3 min. / OFF: 7 min.)  
Contact load capacity: 2.5 A  
Locking force: 500 N  
Breakaway force: 1000 N \*  
Service life: > 10000 cycles  
Locking stroke: 38 mm  
OPEN running speed: 3.3 mm/s  
OPEN running speed - SHEV: 4.2 mm/s  
CLOSED running speed: 3.3 mm/s  
Type of protection: IP 50  
Emission sound pressure level:  $L_pA \leq 70$  dB(A)  
Temperature range: -15 °C (-5 °C \*\*) till +75 °C  
Fire resistance: B300 (30 min / 300 °C)  
Housing: V2A stainless steel  
Connection: 2.5 m silicone cable  
Dimensions (WxHxD): 493 x 25 x 25 mm

\* Breakaway force in release position

\*\* In accordance with VdS 2580

**Scope of supply:**

Drive unit with 2.5 m silicone connection cable with plug adapter, fastening materials for integrated or mounted installation, instruction for use

Brand: D+H Mechatronic AG

Type: VLD 51/038-BSY+

[Planning Support](#)

**Artikelnr.:** 23.060.70

**Quantity:** ..... **Stk**    **Preis:** ..... **€**    **TP:** ..... **€**