

- 1 **D+H Mechatronic (english)**
- 1.1 **CDM Series - PLP drives**
- 1.1.1 **PLP chain drive - CDM-1-PLP - freely configurable**

24 V DC / Special production according to customer requirements

Performance features:

Electromotive drive unit for mounting on the window frame profile.

Drive for electromotive opening and closing of extremely heavy windows and flaps in façade and roof areas.

The drive is equipped with motor electronics controlled via microprocessor. Drive functions and performance features are individually programmable via Powerline (PLP) and the D+H software SCS. High-speed function (HS) for especially fast opening windows in case of fire (SHEV). Low operating noises thanks to the innovative acoustic decoupling of the drive components. Use of a wear-free brushless motor with high efficiency. The drive is available with special chain stabilisation with corrosion protection and lifetime lubrication. Drive chain with symmetrical chain outlet for easy installation and an appealing design due to compact design.

A multi-stage anti-trap protection system (runtime, force/power, stroke) comes standard and can be set via the D+H software SCS. In order to reduce the permanent load on the gasket, a relief of pressure on window gasket is performed after the elements have been closed. Easy installation thanks to a polarity reversal protection connector system.

Technical data:

Operating voltage: 24 V DC / $\pm 15\%$

Current consumption: 2 A

Duty cycle: 30 % (ON: 3 min. / OFF: 7 min.)

Shutdown: Integrated electronic load cut-off

Force of pressure: 1000 N (note pressure load diagram)

Tensile force: 1000 N

Nominal locking force: 3500 N

Service life: 20000 double strokes

Stroke length: **300 mm - 1300 mm** / $\pm 2\%$

OPEN running speed: 7 mm/s

OPEN running speed - SHEV:

11,5 mm/s (with 500 + 600 mm stroke)

15 mm/s (with 700 + 800 mm stroke)

18,5 mm/s (with 1000 mm stroke)

22,5 mm/s (with 1100 + 1200 + 1300 mm stroke)

Type of protection: IP 42

Emission sound pressure level: $L_pA \leq 45$ dB(A)

Temperature range: -15 °C till +75 °C

Fire resistance: B300 (30 min / 300 °C)

Housing: Aluminium

Surface: **on request**

Colour: **on request**

Connection: Silicone cable (must be ordered separately)

Dimensions (WxHxD): **608-841 x 53 x 90 mm**

Scope of supply:

Drive unit, instruction for use

The drive is supplied without connection cable.

Pre-assembled silicone cables with connector plugs must be ordered separately.

Brand: D+H Mechatronic AG

Type: CDM-1-PLP

The D+H partner on site is at your disposal for design variants.

[Planning Support](#)

Artikelnr.: 26.201.00

Quantity: Stk **Preis:** € **TP:** €