

- 1 D+H Mechatronic (english)**
- 1.1 GVL Series**
- 1.1.1 CNV control panel - GVL 8401-K-RC V2**

**24 V DC / 1 A / 2 ventilation groups****Performance features:**

Compact ventilation control panels with an integrated wireless receiver for controlling 24 V DC window drives;  
Configurable ventilation safety function (storage operation OPEN / CLOSED), can be encoded by DIP-switch;  
operation via vent buttons or radio remote control;  
possibility of single/ or central switching (OPEN / CLOSED);  
Input for external controller, e.g. room temperature controller;  
Optional connection to rain detectors or wind / rain sensors without an additional module;  
Surface-mounted design;

**Technical data:**

Supply: 230 V A C / 50 Hz / 56 VA  
Stand-by power: 1 W  
Output: 24 V DC / 1 A  
Mode of operation: Short-time duty (20 % duty cycle)  
Radio frequency: 868.3 MHz / FSK  
Wireless standard:  
ETSI EN 300220-1:2010  
ETSI EN 301489-1:2011  
ETSI EN 301489-3:2002  
Type of protection: IP 66  
Temperature range: -5 °C till +40 °C  
Housing: Polypropylen  
Colour: Light grey (~ RAL 7035)  
Dimensions (WxHxD): 180 x 130 x 77 mm

**Scope of supply:**

Ventilation control panel, instruction for use

Brand: D+H Mechatronic AG  
Type: GVL 8401-K-RC V2

[Planning Support](#)

**Artikelnr.:** 30.241.90

**Quantity:** ..... **Stk**    **Preis:** ..... **€**    **TP:** ..... **€**