

- 1 D+H Mechatronic (english)**
- 1.1 GVL Series**
- 1.1.1 CNV control panel - GVL 8408-M**

**24 V DC / 8 A / 5 ventilation groups****Performance features:**

Expandable ventilation control panel in modular design for controlling 24 V DC window drives;  
Stabilised output voltage;  
Up to 8 A total drive current;  
Configurable ventilation safety function (storage operation OPEN / CLOSED);  
Weather automation for individual groups can be switched ON / OFF;  
Input for external controller, e.g. timer;  
Optional connection to rain detectors or wind / rain sensors without an additional module;

**Technical data:**

Supply: 230 V AC / 50 Hz / 240 VA  
Stand-by power: 2.5 W  
Output: 24 V DC / 8 A  
Mode of operation: Short-time duty (20 % duty cycle)  
Type of protection: IP 30  
Temperature range: -5 °C till +40 °C  
Housing: Plastic  
Colour: White (~ RAL 9016)  
Dimensions (WxHxD): 310 x 310 x 100 mm

**Scope of supply:**

Ventilation control panel in lockable plastic housing with steel sheet door, spare key, instruction for use

Brand: D+H Mechatronic AG

Type: GVL 8408-M

[Planning Support](#)

**Artikelnr.:** 30.202.60

**Quantity:** ..... Stk    **Preis:** ..... €    **TP:** ..... €