

- 1 **D+H Mechatronic (english)**
- 1.1 **VLD Series - Drives**
- 1.1.1 **BSY+ linear lock drive - VLD-BSY+ - freely configurable**

24 V DC / Special production according to customer requirements

Performance features:

Electromotive drive unit for the integrated mounting in the window profile. The drive is equipped with microprocessor-controlled motor and synchronous electronic BSY+ for communication and sequential control in conjunction with D+H BSY+ window opening drives. For operating standard latch pane fittings in the window profile. Can be used for openings for smoke exhaust; D+H Euro SHEV in accordance with EN 12101-2; and for daily ventilation. Drive functions and performance features are individually programmable via the D+H software SCS. VP signal of connected BSY+ opening actuators must be activated. Running and locking direction can be set via slide switch. A manual emergency release is possible with a special tool.

Technical data:

Operating voltage: 24 V DC / ± 20 %
Current consumption: 1 A
Duty cycle: 30 % (ON: 3 min. / OFF: 7 min.)
Contact load capacity: 2.5 A
Locking force: 500 N
Breakaway force: 1000 N *
Service life: > 10000 cycles
Locking stroke: **on request**
OPEN running speed: 3.3 mm/s
OPEN running speed - SHEV: 4.2 mm/s
CLOSED running speed: 3.3 mm/s
Type of protection: IP 50
Emission sound pressure level: $L_p A \leq 70$ dB(A)
Temperature range: -15 °C (-5 °C **) till +75 °C
Fire resistance: B300 (30 min / 300 °C)
Housing: V2A stainless steel
Colour: **on request**
Connection: Silicone cable
Dimensions (WxHxD): 493 x 25 x 25 mm

* Breakaway force in release position

** In accordance with VdS 2580

Scope of supply:

Drive unit with silicone connection cable with plug adapter, fastening materials for integrated or mounted installation, instruction for use

Brand: D+H Mechatronic AG

Type: VLD-BSY+

The D+H partner on site is at your disposal for design variants.

[Planning Support](#)

Artikelnr.: 23.060.80

Quantity: Stk Preis: € TP: €