

- 1 D+H Mechatronic (english)**
- 1.1 GVL Series**
- 1.1.1 CNV control panel - GVL 8401-K-RC V2**

24 V DC / 1 A / 2 ventilation groups**Performance features:**

Compact ventilation control panels with an integrated wireless receiver for controlling 24 V DC window drives;
Configurable ventilation safety function (storage operation OPEN / CLOSED), can be encoded by DIP-switch;
operation via vent buttons or radio remote control;
possibility of single/ or central switching (OPEN / CLOSED);
Input for external controller, e.g. room temperature controller;
Optional connection to rain detectors or wind / rain sensors without an additional module;
Surface-mounted design;

Technical data:

Supply: 230 V A C / 50 Hz / 56 VA
Stand-by power: 1 W
Output: 24 V DC / 1 A
Mode of operation: Short-time duty (20 % duty cycle)
Radio frequency: 868.3 MHz / FSK
Wireless standard:
ETSI EN 300220-1:2010
ETSI EN 301489-1:2011
ETSI EN 301489-3:2002
Type of protection: IP 66
Temperature range: -5 °C till +40 °C
Housing: Polypropylen
Colour: Light grey (~ RAL 7035)
Dimensions (WxHxD): 180 x 130 x 77 mm

Scope of supply:

Ventilation control panel, instruction for use

Brand: D+H Mechatronic AG
Type: GVL 8401-K-RC V2

[Planning Support](#)

Artikelnr.: 30.241.90

Quantity: **Stk** **Preis:** **€** **TP:** **€**