

- 1 D+H Mechatronic (english)**
- 1.1 DXD Series - Drives**
- 1.1.1 BSY+ High-performance rack and pinion drive - DXD 300-BSY+ - freely configurable**

24 V DC / Special production according to customer requirements

Performance features:

Electromotive drive unit for mounting on the window frame profile or sash profile. Drive for electromotive opening and closing of extremely heavy windows, flaps and skylights. Can be used for openings for smoke exhaust; D+H Euro SHEV in accordance with EN 12101-2; and for daily ventilation. The drive is equipped with motor electronics controlled via microprocessor BSY+ for precise synchronous operation one window element. Synchronisation of up to 4 drives. High-speed function (HS) for especially fast opening windows in case of fire (SHEV) (optional). Drive functions and different drive parameters are pre-installed at the factory (according to customer specification) or individually programmable on site via the D+H software SCS. A groove in the drive tube allows flexible installation. Particularly quiet daily ventilation mode. Electronic limit stop and overload cut-off protect the element and the drive from damage. The power supply can be connected either from below or above.

Technical data:

Operating voltage: 24 V DC / $\pm 15\%$
Current consumption: 2.5 A (5 A with HS)
Duty cycle: 30 % (ON: 3 min. / OFF: 7 min.)
Force of pressure:
2000 N continuous load
3000 N short time load
Tensile force: 1000 N
Nominal locking force **: 2800 N
Service life: > 20000 double strokes *
Stroke: **500 mm - 1500 mm**
OPEN running speed: 7.1 mm/s
OPEN running speed - SHEV: 8 mm/s
OPEN running speed - HS: 17 mm/s
CLOSED running speed: 7.1 mm/s
Type of protection: IP 64
Emission sound pressure level: $L_pA \leq 70$ dB(A)
Temperature range: -15 °C (-5 °C ***) till +75 °C
Fire resistance: B300 (30 min / 300 °C)
Tube: Aluminium
Colour: **on request**
Housing motor: Polycarbonate
Colour: **on request**
Connection: Silicone cable

* For vertical use, please consult with D+H Sales!

** Depending on the mounting

*** In accordance with VdS 2580

Scope of supply:

Drive unit with silicone connection cable, instruction for use

Brand: D+H Mechatronic AG

Type: DXD 300-BSY+

The D+H partner on site is at your disposal for design variants.

[Planning Support](#)

Artikelnr.: 20.022.06

Quantity: **Stk** **Preis:** **€** **TP:** **€**