

CPS-M1-040-0204-B-WD



Performance features

- + Power supply of connected drives with up to 40 A total current consumption
- + Tested and certified according to ISO 21927-9, VdS 2581, VdS 2593, VdS 2344, DIN EN 12101-10 and EN 62368-1:2014 + A11:2017, fulfils the building authority requirements in accordance with DIN 18232-9
- + Supply connection and communication using integrated plug connectors
- + Customisable, programmable control panel functions
- + Freely selectable line/group assignment
- + TMA trigger module: 2 independent lines to connect up to 10 SHEV operation panels each and 30 fire detectors
- + Actuator module (AM-B): 2 independent groups for connecting drives, each with a total maximum current of 10 A

Approvals / Certificates

Find out about permission details from your D+H Partner.



Article also available with the following permissions under other article numbers. Technical data may deviate.



Technical data

CPS-M1-040-0204-B-WD

Supply	230 V AC / 50 Hz / 1040 VA
Stand-by power	8,5 W
Output	24 V DC / 40 A
Ripple	< 50 mVss
Mode of operation monitoring	Pulse operation
Mode of operation Alarm / Ventilation	Short-time duty 30 % duty cycle
Type of protection	IP 54
Temperature range	-5 °C ... +40 °C
Number of TMA	1
Number of AM-B	2
Line / Group	2 / 4
Housing	Steel sheet
Colour	Light grey (~ RAL 7035)
W x H x D	600 x 800 x 260 mm
Battery type	Typ 6 (2x)
Weight	24.1 kg
Remark	Without touch panel
Art. No.	31.700.33

Batteries must be ordered separately.

Example of application

