

CPS-B1-5-0101







Performance features

- + Compact SHEV control panel, specifically for stairwells
- + Tested and certified according to ISO 21927-9, VdS 2581, VdS 2593, VdS 2344, DIN EN 12101-10 and EN 62368-1:2014 + A11:2017, fulfils the building authority requirements in accordance with DIN 18232-9
- + Up to 5 A total drive current
- + Stabilised output voltage
- Switchable SHEV safety functions: Fault equal to alarm, SHEV retriggering function and smoke detector remote

- + Integrated comfort functions for daily ventilation
- + Optional connection to rain detectors or wind / rain sensors without an additional module
- Connection of up to 8 SHEV operation panels and 8 fire detectors per line (Only detectors permitted by D+H may be used)
- + Min. 72 hr battery backup supply

Approvals / Certificates

Find out about permission details from your D+H Partner.





Technical data

CPS-B1-5-0101

Supply	230 V AC / 50 Hz / 145 VA
Stand-by power	< 2 W
Output	24 V DC / 5 A
Mode of operation monitoring	Continuous duty
Mode of operation Alarm / Ventilation	Short-time duty 30 % duty cycle
Type of protection	IP 30
Temperature range	-5 °C +40 °C
Line / Group	1/1
Housing	Plastic
Colour	White (~ RAL 9016)
WxHxD	310 x 310 x 104 mm
Battery type	Typ 8 (2x)
Weight	1.92 kg
Art. No.	30.119.15

Batteries must be ordered separately.

Example of application

