


# RZN 4408-M



## Performance features

- + Compact SHEV control panel - AdComNet ready
- + Tested and certified according to ISO 21927-9, VdS 2581, VdS 2593, VdS 2344 and DIN EN 12101-10, fulfils the building authority requirements in accordance with DIN 18232-9
- + Up to 8 A total drive current
- + Stabilised output voltage
- + Switchable SHEV safety functions: Fault equal to alarm, SHEV retriggering function and smoke detector remote reset
- + Option to combine SHEV / building alarm function
- + Integrated comfort functions for daily ventilation
- + Optional connection to rain detectors or wind / rain sensors without an additional module
- + Connection of up to 8 SHEV operation panels and 14 fire detectors per line (Only detectors permitted by D+H may be used)
- + Min. 72 hr battery backup supply

# Approvals / Certificates

Find out about permission details from your D+H Partner.



Article also available with the following permissions under other article numbers. Technical data may deviate.



## Technical data

### RZN 4408-M

<b>Supply</b>	230 V AC / 50 Hz / 240 VA
<b>Stand-by power</b>	5 W
<b>Output</b>	24 V DC / 8 A
<b>Ripple</b>	< 2 V <sub>ss</sub>
<b>Mode of operation monitoring</b>	Continuous duty
<b>Mode of operation Alarm / Ventilation</b>	Short-time duty 30 % duty cycle
<b>Temperature range</b>	-5 °C ... +40 °C
<b>Line / Group</b>	2 / 3
<b>Battery type</b>	Typ 8 (2x)
<b>Weight</b>	2.9 kg
<b>Remark</b>	With alarm devices = Akku Typ 3 (2x)
<b>Art. No.</b>	30.117.20

Batteries must be ordered separately.

# Example of application

