

- 1 D+H Mechatronic (english)**
- 1.1 CDC Series - ACB drives**
- 1.1.1 ACB chain drive - CDC-0252-0350-1-ACB S1-L ON**

**24 V DC / 0.6 A / 250 N / 350 mm stroke**

Drive for the integrated, hidden installation in the window profile and for mounted installation. For the convenient motorised opening and closing of windows and flaps. Useable for smoke exhaust (SHEV), D+H Euro SHEV in accordance with EN 12101-2 as well as for natural ventilation. 24 V DC version in conjunction with the 230 V AC drive (Main 2).

**Performance features:**

Integrated, freely programmable electronic shut-down device to prevent a defect in the event of an overload on the window or drive;

High precision synchronised electronics for running 2 drives simultaneously;

Low operating noises thanks to the innovative acoustic decoupling of the drive components;

Corrosion protected, hardened steel chain with rigid backing and lifetime lubrication;

High-speed function (HS) for opening windows especially fast in case of fire (SHEV);

Adjustable, multi-stage anti-trap protection system (runtime, force/power, stroke);

Gasket protection thanks to the automatic relief of pressure on window gasket after a closing process;

Easy installation thanks to s polarity reversal protection connector system;

Due to loop-through option (DS) a connection with D+H locking drives is possible as well as an open bus communication via ACB (Advanced Communication Bus) e.g. in a building management system (building automation);

Custom configuration possible via D+H software SCS;

**Functional description ACB**

Secure SHEV-BUS communication via an encrypted data transfer between D+H Mechatronic AG control panels and drives.

Directly controlling the drive using the ACB is possible. The drive is set to the pole change operation at the factory by default.

Control with perfect positioning and feedback including information about the CURRENT position.

Status messages such as the drive's OPEN and CLOSED signal are issued directly via ACB communication.

The general status of the drive, such as the total travel path, number of control units, diagnostics and the emergency drive function can be evaluated.

**Technical data:**

Operating voltage: 24 V DC /  $\pm 15\%$

Current consumption: 0.6 A

Duty cycle: 30 % (ON: 3 min. / OFF: 7 min.)

Shutdown: Integrated electronic load cut-off

Configuration: Sub 1

Design: Left

Force of pressure: 250 N

Tensile force: 250 N

Nominal locking force \*\*: 1500 N

Service life: 20000 double strokes \*

Stroke length: 350 mm /  $\pm 2\%$

OPEN running speed: 6.7 mm/s

OPEN running speed - SHEV: 9.4 mm/s

CLOSED running speed: 5 mm/ s (according to protection class 3, Machinery Directive 2006/42/EG)

Type of protection: IP 32

Emission sound pressure level:  $L_p A \leq 35$  dB(A)

Temperature range: -15 °C (-5 °C <sup>\*\*\*</sup>) till +75 °C  
Fire resistance: B300 (30 min / 300 °C)  
Opening mechanic: Maintenance-free, corrosion protected hardened push linked chain with lifetime lubrication  
Housing: Aluminium  
Surface: Powder-coated  
Colour: White aluminium (~ RAL 9006)  
End caps, plug: Plastic, grey (~ RAL 9006)  
Connection: 2.5 m silicone cable  
Dimensions (WxHxD): 545 x 30 x 39 mm

\* For vertical use, please consult with D+H Sales!

\*\* Depending on the mounting

\*\*\* In accordance with VdS 2580

**Scope of supply:**

Drive unit with 2.5 m silicone connection cable with system plug, instruction for use

Brand: D+H Mechatronic AG

Type: CDC-0252-0350-1-ACB S1-L ON

[Planning Support](#)

**Artikelnr.:** 26.105.11

**Quantity:** ..... Stk    **Preis:** ..... €    **TP:** ..... €