

1 D+H Mechatronic (english)**1.1 VLD Series - Drives****1.1.1 Linear lock drive - VLD 51/038****24 V DC / 1 A / 500 N / 38 mm stroke****Performance features:**

Electromotive drive unit for the integrated mounting in the window profile. For operating standard latch pane fittings in the window profile. A connection of D+H window drives with "BRV" message is possible. Can be used for openings for smoke exhaust; D+H Euro SHEV in accordance with EN 12101-2; and for daily ventilation. Switching current for window drives up to 2.5 A, daisy-chain contacts 60 V / 1 A available e.g. for alarm or drive notifications. Running and locking direction can be set via slide switch. A manual emergency release is possible with a special tool.

Technical data:

Operating voltage: 24 V DC / $\pm 20\%$
Current consumption: 1 A
Duty cycle: 30 % (ON: 3 min. / OFF: 7 min.)
Contact load capacity: 2.5 A
Locking force: 500 N
Breakaway force: 1000 N *
Service life: > 10000 cycles
Locking stroke: 38 mm
OPEN running speed: 4.2 mm/s
CLOSED running speed: 4.2 mm/s
Type of protection: IP 50
Emission sound pressure level: $L_p A \leq 70$ dB(A)
Temperature range: -15 °C (-5 °C **) till +75 °C
Fire resistance: B300 (30 min / 300 °C)
Housing: V2A stainless steel
Connection: 2.5 m silicone cable
Dimensions (WxHxD): 493 x 25 x 25 mm

* Breakaway force in release position

** In accordance with VdS 2580

Scope of supply:

Drive unit with 2.5 m silicone connection cable with plug adapter, fastening materials for integrated or mounted installation, instruction for use

Brand: D+H Mechatronic AG

Type: VLD 51/038

[Planning Support](#)

Artikelnr.: 23.060.50

Quantity: **Stk** **Preis:** **€** **TP:** **€**